

## **FDTD analysis of nonlinear PBG waveguides for optical circuit applications**

I. S. Maksymov, L. F. Marsal, and J. Pallarès,  
DEEEA, Universitat Rovira I Virgili, Països Catalans 26, 43007 Tarragona, Spain.

Nonlinear PBG structures have attracted considerable attention as an optical material which is expected to play an important role in the future of the integrated optical circuits. In this study, a finite-difference time-domain (FDTD) method based on numerical simulation of oscillating dipole radiation [1] is used for Kerr-like nonlinear PBG waveguide analysis. In order to calculate dispersion characteristics of a PBG waveguide, the super-cell that includes an imperfect part of the PBG structure is used. A cubic equation is solved analytically within the main body of the FDTD algorithm to calculate the electric field intensity, which induces the nonlinearity [2].

A numerical tool based on the presented method can be used to analyze various components for integrated optical circuits. These components include PBG-based nonlinear directional couplers, all-optical switches, etc. Their functionality is explained through the analysis of dispersion characteristics and verified by conventional FDTD simulations. Some examples will be presented.

[1] I. S. Maksymov, L. F. Marsal and J. Pallarès, *Opt. Commun.*, (published online, 2005).

[2] I. S. Maksymov, L. F. Marsal and J. Pallarès, *Opt. Quant. Electronics*, (special issue OWTNM-2004, to be published in 2005).